

Spécifications moquettes axminster Master Weaver / Crossley holdings
Axminster carpets technical specifications

Qualité Axminster / Axminster Quality : 7 x 10 – 3/40's – R775/3	
Construction / Constuction	Moquette tissage axminster / Axminster weave
Composition velours / Pile material :	80% laine/20% nylon – 80% wool/20% nylon
Serrage trame / Rows :	39.4 Rangées/10cm 10 Rows/inch
Serrage chaîne / Pitches :	27,6 Chaines/10cm 7 Pitches/inchs
Tufts/m ²	± 108.744 /m ²
Fil – Yarn :	3/40's (Dewsbury) - R775/3 (Tex)
Largeurs de tissage possibles / Carpet Widths :	0.69m / 27" - 0.91m / 3' - 1.37m / 4'6" 1.83m / 6' - 2m / 6'7" - 2.74m / 9' 3.66 m / 12' - 4.00m / 13'1"
Dossier/Backing :	Jute (ou/or polypro) & Poly coton
Hauteur velours / Pile height :	± 7,1mm - .281 inch
Hauteur totale / Total height :	± 10mm - .400 inch
Poids velours / Pile weight :	± 1.800 grs/m ² / ± 53,09 oz/yard ²
Poids Total/ Total weight :	± 2.800 grs/m ² (dossier jute / jute backing) ± 2.600 grs/m ² (dossier polypro /polypro backing)
Classements Euroclass et Maritime Fire rating and Marine certification:	Cfl-S1 and IMO certified